

⚡ Specifications

Nominal Voltage(V)

12V

Nominal Capacity

20 hour rate	(1.2A	to	10.50V)	24Ah
10 hour rate	(2.28A	to	10.50V)	22.8Ah
5 hour rate	(4.08A	to	10.20V)	20.4Ah
1 C	(24A	to	9.60V)	13.6Ah
3 C	(72A	to	9.60V)	9.6Ah

Weight

Approx. 7.14kg(15.7Lbs.)

Internal Resistance (at 1KHz)

Approx. 8 mΩ

Maximum Discharge Current for

5 seconds: 360A

Charging Methods at 25°C(77°F)

Cycle use:	
Charging Voltage	14.4 to 15.0V
Coefficient -5.0mV/°C/cell	
Maximum Charging Current :	7.2A
Standby use:	
Float Charging Voltage	13.5 to 13.8V
Coefficient -3.0mV/°C/cell	

Operating Temperature Range

Charge	-15°C(5°F)	to	40°C(104°F)
Discharge	-15°C(5°F)	to	50°C(122°F)
Storage	-15°C(5°F)	to	40°C(104°F)

Charge Retention (shelf life) at 20°C(68°F)

1 month	92%
3 month	90%
6 month	80%

Case Material

ABS UL94 HB
Option: Flammability resistance of (UL94 V-0)

Design Life

3-5 Years.

Terminal

F6



⚡ Dimensions

Length (L) 181±2-1 (7.13±0.08-0.04)


Width (W) 77.5±2-1 (3.05±0.08-0.04)

Height (H) 169±2-1 (6.65±0.08-0.04)


Overall Height (HT) 169±2-1 (6.65±0.08-0.04)

Recommended torque value M5: 4 N-m (41kgf-cm)


Maximum allowable torque value M5: 6 N-m (61kgf-cm)




(V) FOR 12V BATTERY **Discharge Time VS. Discharge Current (25°C)**




Effect of Temperature on Capacity 25°C(77°F)



Capacity Retention Characteristic



Cycle Service Life



Trickle (or float) Service Life

